

1. IDENTIFICATION OF PREPARATION

Product Code and Names:

75110 - Terrafix Grey	75115 - Terrafix Super Grey	75120 - Terrafix White
75125 - Terrafix Super White	75160 - Rapidfix W1	75165 - Rapidfix F1
75210 - Terragrout	75220 - Terragrout WJ	75310 - Blockfix ALC Grey
75311 - Blockfix ALC White	75410 - Styrobond DP	75411 - Ambient Adhesive DP
75412 - Styrobond DP High Build	75417 - Styrobond FM	75419 - Styrobond DP CONC
75420 - Styrofix	75421 - Styrofile	75422 - Styrogrount
75425 - Styrofix CONC	75430 - Tilobond Fine White	75435 - Tilobond Fine Grey
75440 - Tilobond Standard White	75445 - Tilobond Standard Grey	75510 - Maxifix White
75520 - Maxifix Grey	75522 - Maxifix CONC	75540 - Terrafix W11 Grey
75545 - Terrafix W11 White	76110 - Weathercoat Powder Grey	76115 - Weathercoat Powder White
76120 - Terracrete Part A	76130 - Weathercoat SP	77111 - Maximix Grey
76130 - Weathercoat SP	77111 - Maximix Grey	77114 - Handymix Putty Grey A100
77114 - Handymix Putty Grey A100	77121 - Handymix Putty Grey B100	77122 - Handymix Putty White B200
77128 - Styroskim Powder (Pt A)	77330 - Flexipave Patching Compound Powder	77610 - Sprayplaster CM
77611 - Sprayplaster CM-XT	77650 - Keybond	

Chemical Name: Mixture of calcium oxide, polymers, fillers cement, and additives

CAS Number: Blend

Identification of Company:

<p>RUSSIA: OOO Terraco Sweden Ltd, Russia Tel: +7 (0)495 9212 237 Fax: +7 (0)495 6273 881 E-mail: adm@terraco.ru Web: www.terraco.ru</p> <p>OOO Terraco Vostok Ltd Tel: +7 (0)4212 410563 Fax: +7 (0)4212 410591 E-mail: terracovostok@terraco.khn.ru Web: www.terraco.com</p> <p>CHINA: Terraco Architectural Coatings China Co., Ltd. Tel: +86 (0)20 8759 4742 Fax: +86 (0)20 8526 8056 E-mail: sales@terraco.com.cn Web: www.terraco.com.cn</p> <p>Terraco Chemical (Shanghai) Co., Ltd. Tel: +86 (0)21 621020 48 / 18 Fax: +86 (0)21 625205 47 Email: sales@terraco.com.cn Web: www.terraco.com.cn</p> <p>PAKISTAN: Terraco Pakistan Pvt. Ltd. Tel: +92 (0)42 3529 70 56-8 Fax: +92 (0)42 3529 70 55 Email: terraco@terraco.pk Web: www.terraco.com</p>	<p>JORDAN: Jordan Swedish Polymers Industrial Corp. Tel: +962 (0)6 553 8751 Fax: +962 (0)6 553 6560 E-mail: terraco@nol.com.jo Web: www.terraco.jo</p> <p>EGYPT: Terraco Egypt Chemical Industries S.A.E. Tel: +20 (0)22 29184 53 / 57 / 58 Fax: +20 (0)22 29184 80 E-mail: terraco@terraco.com.eg Web: www.terraco.com.eg</p> <p>UAE: Terraco UAE Ltd Tel: +971 (0)4 326 2699 Fax: +971 (0)4 326 2733 E-mail: terraco@terraco.ae Web: www.terraco.com</p> <p>TURKEY: Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS Tel: +90 (0)222 236 0423 Fax: +90 (0)222 236 0425 E-mail: terraco@terraco.com.tr Web: www.terraco.com.tr</p>	<p>THAILAND: Terraco Industry (Thailand) Limited Tel: +66 (0)2 946 68 56 / 58 Fax: +66 (0)2 946 68 59 E-mail: terraco@terraco.co.th Web: www.terraco.com</p> <p>VIETNAM: Terraco Vietnam Co., Ltd Tel: +84 (0)650 3 820 100 Fax: +84 (0)650 3 820101 E-mail: terraco@terraco.com.vn Web: www.terraco.com</p> <p>SOUTH KOREA: Terraco Korea Co., Ltd Tel: +82 (0) 2 5611 551 Fax: +82 (0)2 5671 771 E-Mail: terraco@terraco.co.kr Web: www.terraco.co.kr</p> <p>IRELAND: Terraco Technical Centre, Ireland Tel: +353 (0) 404 66555 Fax: +353 (0) 404 66654 E-mail: technical-centre@terraco.com Web: www.terraco.com</p>
--	--	---

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Amount	CAS Number
Cement:	<50.0%	65997-15-1
Calcium Oxide:	<5.0%	1305-78-8
Vinyl/Ethylene Polymer:	<5.0%	Proprietary
Silica:	<75.0%	14808-60-7

3. HAZARDS IDENTIFICATION

Not classified as dangerous for supply. Avoid inhalation of dust during mixing.

Potential Health Effects

Eye	Contact may cause irritation.
Skin	As this product contains Calcium oxide, it may cause skin burns, irritation and possible allergic reaction.
Inhalation	Prolonged or excessive inhalation of crystalline silica may cause lung damage.
Ingestion	Ingestion is not considered a potential route of exposure.
Target Organs	Skin, eyes, respiratory system.
Medical Conditions Aggravated by Exposure	Bronchitis and Asthma.

4. FIRST AID MEASURES

General	In all cases of doubt or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Eye Contact	Flush eye with water for 15 minutes, holding eye lids apart. Get medical attention if irritation develops.
Skin Contact	Remove contaminated clothing. Wash skin with soap and water or a proprietary skin cleaner.
Inhalation	If exposed to excess levels of dust remove to fresh air, and get medical attention if adverse symptoms persist.
Ingestion	If accidentally swallowed, obtain immediate medical attention. Show this safety data sheet. Do not induce vomiting. If conscious give milk or water to drink.

5. FIRE FIGHTING MEASURES

Flammable Properties	C.O.C. Flash Point:	None
	T.C.C. Flash Point:	None
	Auto ignition temperature:	None
Flammable Limits In Air	L.E.L.	None
	U.E.L.	None
Extinguishing Media	Use extinguishing media appropriate for surrounding fire. If engulfed by ongoing fire do not allow fire fighting run off to enter drains or watercourses. As in any fire wear self-contained breathing apparatus, pressure demand MSHA/NIOSH (approved or equivalent) and full protective gear.	

6. ACCIDENTAL RELEASE MEASURES

Safeguards (Personnel)	Exclude all non-essential personnel. Wear appropriate personal protective equipment.
Initial Containment	Absorb spills with inert material, allow to solidify and scrape up. Do not allow to enter drains or watercourses, clean preferably with a detergent. Do not use solvents. If the product accidentally enters, rivers, lakes, drains or sewers, the Local Authority should be contacted immediately.

7. HANDLING AND STORAGE

General	Smoking, Eating and Drinking should be prohibited in areas of storage or use. Never use pressure to empty the container. Good housekeeping and regular safe removal of waste materials are recommended.
Recommended Storage Temperature	Minimum: 5C (35.6F) Maximum: 40C (104.0F)
Shelf Life	12 months in original sealed containers.
Handling (Personnel)	Avoid breathing dust. Avoid prolonged contact with skin or eyes.
Storage Precautions	Keep dry. Keep out of reach of children. Store separately from Oxidising Agents, and strongly acidic or alkaline materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits	No information presently available.
Engineering Controls	If user operations generate dust, fumes or mist, use local exhaust ventilation and good general extraction.
Personal Protection	
Respiratory Protection	If airborne concentrations exceed the OSHA TWA, a NIOSH approved dust mask is recommended.
Skin Protection	Wear protective gloves to minimise skin contamination.
Eye Protection	Splashes of mixed for use product and dust may cause irritation, it is recommended that protective goggles should be worn.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	Powder
Odour	Slight cement odour
Boiling Point	N/A
Solubility In Water	< 1.0%
Specific Gravity	2.5-3.0 (Water =1)
pH	11-13
Volatile Organic Compounds	0gm./lt.

10. STABILITY AND REACTIVITY

Stability	Stable.
Polymerisation	Product will not undergo polymerisation.
Incompatibility With Other Material	Incompatible with oxidising agents and strongly acidic and alkaline materials.

11. TOXICOLOGICAL INFORMATION

There is no data available on the products themselves.

Repeated or prolonged contact may lead to skin burns, irritation and possible allergic reaction.

Splashes in eyes may cause irritation and reversible local damage.

Ingestion may result in sore throat, abdominal pain or nausea.

12. ECOLOGICAL INFORMATION

There is no data available on the products themselves. They should not be allowed to enter drains or watercourses.

13. DISPOSAL CONSIDERATIONS

Do not allow to enter drains and watercourses or anywhere that may affect ground or surface waters. Wastes including emptied containers should be disposed of in accordance with the regulations of the Local Authority.

14. TRANSPORT INFORMATION

To transport within the user's premises, always use closed containers that are secure and upright. Ensure that operational personnel know what to do in event of spillage.

D.O.T. SHIPPING NAME:	Not Applicable
------------------------------	----------------

D.O.T. HAZARD CLASS:	Non-Hazardous
-----------------------------	---------------

15. REGULATORY INFORMATION

The products are determined as not being dangerous for supply according to current Chemicals Hazard Information and Packing Regulations in force.

The information contained in this Material Safety Data Sheet, does not substitute the user's own responsibility to carry out an assessment of work place risks as may be required by Health and Safety Legislation.

16. OTHER INFORMATION

The products should not be used for purposes other than those shown on the manufacturer's product labels and technical data sheets. As the specific conditions of use are outside the supplier's control; the user is responsible for ensuring compliance with the relevant legislation in the territory of use.

The information contained in this Material Safety Data Sheet, is based on the current state of knowledge and current state of Legislation. It provides guidance on Health Safety and Environmental aspects of the products, and should not be taken as a guarantee of technical performance or suitability for particular applications.

Approved by:	J. Carey - Group Technical Director.
Approval date:	24/06/2011
Supersedes:	18/04/2011
Number:	MSDS No. 1004

This information is furnished without warranty, expressed or implied, except that it is accurate to the best of TERRACO's knowledge. The data on this sheet are related only to the specific materials designated herein. TERRACO assumes no legal responsibility for use or reliance upon this data.